## NSN 3020-00-498-7303

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-498-7303

**Body Style:** Webbed, offset, solid **Attachment Method:** Mounting hole **Pitch Diameter:** 0.9380 inches **Teeth Quantity:** 75 **Bore Style:** Plain both ends Mounting Hole Thread Series Designator: Unc transversely through hub, first end Mounting Hole Thready Qty Per Inch (tpi): 56 transversely through hub, first end Mounting Hole Thread Size: 0.086 inches transversely through hub, first end Mounting Hole Type And Quantity: 2 threaded transversely through hub, first end **Outside Diameter:** 0.963 inches Nominallength: 0.187 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.125 inches first end **Body Recess Depth:** 0.031 inches second end Face Width: 0.062 inches **Bore Diameter:** 0.500 inches both ends Hub Style Designator: Plain first end Hub Diameter: 0.656 inches first end Material: Steel comp 303 **Material Specification:** 

Qq-s-764, type 303, cond a federal specification single material response

## NSN 3020-00-498-7303

Spur Gear - Page 2 of 2

Style Designator:

Protruding hub, recessed body

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A27300

