## NSN 3020-00-498-9927

Spur Gear - Page 1 of 2



27

View Online at https://aerobasegroup.com/nsn/3020-00-498-99
Body Style:
Plain, solid
Attachment Method:
Mounting hole
Pitch Diameter:
Between 2.6990 inches and 2.7000 inches
Teeth Quantity:
216
Bore Style:
Plain both ends
Mounting Hole Thread Series Designator:
Unf transversely through hub, first end
Mounting Hole Thready Qty Per Inch (tpi):
80 transversely through hub, first end
Mounting Hole Thread Size:
0.060 inches transversely through hub, first end
Mounting Hole Type And Quantity:
4 threaded transversely through hub, first end
Outside Diameter:
2.723 inches
Nominallength:
1.065 inches
Tooth Form:
Standard
Pressure Angle:
20.0000 degrees
Distance Between Body Face And Protruding Hub End:
0.940 inches first end
Face Width:
0.494 inches
Bore Diameter:
2.000 inches both ends
Hub Style Designator:
Plain second end
Hub Diameter:
2.644 inches second end
End Length:
0.031 inches first end
End Diameter:
2 249 inches first end

First Step Length: 0.909 inches first end

## NSN 3020-00-498-9927

Spur Gear - Page 2 of 2



First Step Diameter:
2.644 inches first end
Material:
Aluminum alloy 6061
Material Specification:
Qq-a-250/11, t6 federal specification single material response
Surface Treatment:
Anodize
Surface Treatment Specification:
Mil-a-8625 military specification single treatment response
Style Designator:
Protruding hubs
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A27300
Mil-std (military Standard):
Mil-a-8625 spec.