## NSN 3020-00-499-4242

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-499-4242

Body Style:
Plain, solid
Attachment Method:
Mounting hole
Pitch Diameter:
0.7500 inches
Teeth Quantity:
22
Bore Style:
W/ keyway both ends
Mounting Hole Thread Series Designator:
Unc axially through hub, first end
Mounting Hole Thready Qty Per Inch (tpi):
18 axially through hub, first end
Hardness Rating:
55.0 rockwell c and 60.0 rockwell c
Mounting Hole Thread Size:
0.312 inches axially through hub, first end
Mounting Hole Type And Quantity:
2 threaded axially through hub, first end
Outside Diameter:
3.000 inches
Tooth Form:
Standard
Pressure Angle:
20.0000 degrees
Distance Between Body Face And Protruding Hub End:
0.3750 inches first end
Face Width:
0.750 inches
Bore Diameter:
0.8755 inches both ends
Keyway Width:
0.1870 inches both ends
Distance From Bore Center To Keyway Bottom:
0.5295 inches both ends
Hub Style Designator:
Plain both ends
Hub Diameter:
1.6625 inches first end
Mounting Hole Diameter:
0.125 inches axially through hub, first end

## **NSN 3020-00-499-4242** Spur Gear - Page 2 of 2

Fiig: A27300



Special Features:
Position of keyway must be centered between teeth
Material:
Steel
Material Specification:
Qq-s-624 federal specification single material response
Style Designator:
Protruding hubs
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No