NSN 3020-00-499-4330



Spur Gear - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/3020-00-499-4330 **Body Style:** Webbed, offset, solid **Attachment Method:** Mounting hole Pitch Diameter: 0.8432 inches **Teeth Quantity:** 54 **Bore Style:** Plain both ends **Mounting Hole Thread Series Designator:** Unc transversely through hub, first end **Mounting Hole Thread Size:** 0.060 inches transversely through hub, first end

Mounting Hole Type And Quantity:

1 threaded transversely through hub, first end

Outside Diameter:

0.8740 inches

Tooth Form:

Standard

Pressure Angle:

20.0000 degrees

Distance Between Body Face And Protruding Hub End:

0.0450 inches second end

Face Width:

0.120 inches

Bore Diameter:

0.0912 inches both ends

Hub Style Designator:

Plain second end

Hub Diameter:

0.2500 inches first end

First Groove Width:

0.1300 inches first end

First Groove Diameter:

0.1900 inches first end

Distance From End To First Groove:

0.0950 inches first end

Material:

Aluminum alloy

Material Specification:

Qq-a-225/8 alloy 6061 t6 federal specification single material response

NSN 3020-00-499-4330

Spur Gear - Page 2 of 2



_	•		_			
ن	ırfa	\sim	Irο	o+n	20r	٠.
u	ai ia	uc.	116	аш	161	IL.

Anodize

Style Designator:

Protruding hubs

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A27300