## NSN 3020-00-499-4330

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-499-4330

**Body Style:** Webbed, offset, solid **Attachment Method:** Mounting hole **Pitch Diameter:** 0.8432 inches **Teeth Quantity:** 54 **Bore Style:** Plain both ends Mounting Hole Thread Series Designator: Unc transversely through hub, first end **Mounting Hole Thread Size:** 0.060 inches transversely through hub, first end Mounting Hole Type And Quantity: 1 threaded transversely through hub, first end **Outside Diameter:** 0.8740 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.0450 inches second end Face Width: 0.120 inches **Bore Diameter:** 0.0912 inches both ends Hub Style Designator: Plain second end **Hub Diameter:** 0.2500 inches first end First Groove Width: 0.1300 inches first end **First Groove Diameter:** 0.1900 inches first end **Distance From End To First Groove:** 0.0950 inches first end Material: Aluminum alloy **Material Specification:** 

Qq-a-225/8 alloy 6061 t6 federal specification single material response

# NSN 3020-00-499-4330

Spur Gear - Page 2 of 2

Surface Treatment:

Anodize

#### Style Designator:

Protruding hubs

Shelf Life:

N/a

### Unit Of Measure:

---

#### Demilitarization:

No

Fiig:

A27300

