## NSN 3020-00-500-6037

Flat Pulley - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-500-6037 **Outside Diameter:** 0.740 inches **Overall Length:** 0.370 inches **Outside Diameter:** 0.800 inches **Thread Size:** 0.086 in.-56 **Bore Diameter:** 0.125 inches Bore Length: 0.370 inches Flange Width: 0.020 inches Flange Quantity: **Securing Hole Quantity:** 2 **Material And Location:** Aluminum alloy, qq-a-250/4, alloy 2024, t351 Face Width: 0.220 inches Design Form: Plain **Bore Type:** Straight Bearings: Not included **Counterbore Feature:** Not included **Hole Location:** 0.075 in. From hub end, 90 degrees apart **Keying Facility:** Not included **Securing Method:** Threaded hole **Split Hub Feature:** 

Not included **Lightening Hole:** Included **Integral Cooling Vane:** Not included

## **NSN 3020-00-500-6037** Flat Pulley - Page 2 of 2



Crown Face:
Not included
Rim Type:
Solid
Flange Location:
Outside
Bore Feature:
Included
Protruding Hub Characteristic:
Plain
Securing Location:
Aa end
Hub End Outside Diameter And Location:
0.375 inches aa end
Distance From Outside Flange/rim To Hub End And Location:
0.150 inches aa end
Special Features:
Two 0.031 in. W by 0.048 in. Deep slots on opposite sides of pulley rims 0.570 in. Apart
Surface Treatment:
Anodize
Style Designator:
Plain
Surface Treatment:
Anodized
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
T353-a