NSN 3020-00-506-4868

Sprocket Wheel - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-506-4868

Outside Diameter:
Between 1.733 inches and 1.738 inches
Overall Length:
Between 0.615 inches and 0.635 inches
Keyway Width:
Between 0.126 inches and 0.128 inches
Bore Diameter:
Between 0.624 inches and 0.625 inches
Bore Length:
Between 0.615 inches and 0.635 inches
Distance From Center Of Bore To Bottom Of Keyway:
Between 0.375 inches and 0.379 inches
Pitch Diameter:
1.667 inches
Face Width:
Between 0.250 inches and 0.260 inches
Design Form:
Plain
Bore Type:
Straight
Counterbore Feature:
Not included
Keying Facility:
Included
Keying Facility Type:
Keyway
Lightening Hole:
Not included
Protruding Hub Characteristic:
Plain
Belt/chain/film Size For Which Designed:
Block chain
Teeth Row Quantity:
1
Teeth Quantity Per Row:
20
Asa Standard Chain Number:
100
Hardness Rating Test Method:
Not rated
Bore Bearing:
Not included

NSN 3020-00-506-4868 Sprocket Wheel - Page 2 of 2



Hub External Keyway:
Not included
Tooth Pitch:
0.250 inches
Hub End Outside Diameter And Location:
1.365 inches aa end and 1.385 inches aa end
Distance From Outside Flange/rim To Hub End And Location:
0.365 inches aa end and 0.375 inches aa end
Material:
Lead alloy
Material:
Lead alloy
Quantity:
1
Style Designator:
Plain
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Fiig:
Т353-с