## NSN 3020-00-509-6007



Spur Gear - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/3020-00-509-6007 **Body Style:** Webbed, offset, solid **Spline Quantity:** 26 both ends **Attachment Method:** Mounting hole Pitch Diameter: 2.6990 inches **Teeth Quantity:** 36 **Bore Style:** Involute spline both ends **Spline Pitch Diameter:** 1.3000 inches both ends **Backlash Designation:** Grade a **Hardness Rating:** 80.0 rockwell a and 85.0 rockwell a teeth **Mounting Hole Type And Quantity:** 2 plain axially through body, first end **Outside Diameter:** 2.834 inches Nominallength: 0.760 inches **Tooth Form:** Standard **Pressure Angle:** 22.5000 degrees Distance Between Body Face And Protruding Hub End: 0.480 inches first end **Body Recess Depth:** 0.070 inches second end **Face Width:** 0.280 inches **Bore Diameter:** 1.377 inches both ends **Hub Style Designator:** Plain first end **Hub Diameter:** 

1.675 inches first end **Mounting Hole Diameter:** 0.156 inches axially through body, first end

## **NSN 3020-00-509-6007** Spur Gear - Page 2 of 2

Fiig: A27300



Material:
Steel comp e9310
Material Specification:
Ams 6260 assn standard single material response
Style Designator:
Protruding hub, recessed body
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No