NSN 3020-00-517-0834

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-517-0834

Body Style:							
Plain, solid							
Attachment Method:							
Mounting hole							
Pitch Diameter:							
0.3305 inches							
Teeth Quantity:							
16							
Bore Style:							
Plain both ends							
Mounting Hole Thread Series Designator:							
Unc transversely through hub, first end							
Mounting Hole Thready Qty Per Inch (tpi):							
56 transversely through hub, first end							
Mounting Hole Thread Size:							
0.086 inches transversely through hub, first end							
Mounting Hole Type And Quantity:							
1 plain transversely through hub, first end							
Outside Diameter:							
0.372 inches							
Nominallength:							
0.260 inches							
Tooth Form:							
Standard							
Pressure Angle:							
20.0000 degrees							
Distance Between Body Face And Protruding Hub End:							
0.160 inches first end							
Face Width:							
0.100 inches							
Bore Diameter:							
0.125 inches both ends							
Hub Style Designator:							
Pinned first end							
Pinned first end							
Pinned first end Hub Diameter:							
Pinned first end Hub Diameter: 0.280 inches first end							
Pinned first end Hub Diameter: 0.280 inches first end Mounting Hole Diameter:							
Pinned first end Hub Diameter: 0.280 inches first end Mounting Hole Diameter: 0.040 inches transversely through hub, first end							

_ ...

Copper alloy 544

NSN 3020-00-517-0834

Spur Gear - Page 2 of 2



١	V	ate	ria	l Sr	heci	fic	atio	n
ľ	٧I	alt	:i iai	I OL	JECI	III	ลแบ	и.

Astm b139, 4st, grade b2 assn standard single material response

Style Designator:

Protruding hub

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

A27300