## NSN 3020-00-517-0834

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-517-0834

**Body Style:** Plain, solid **Attachment Method:** Mounting hole **Pitch Diameter:** 0.3305 inches **Teeth Quantity:** 16 **Bore Style:** Plain both ends Mounting Hole Thread Series Designator: Unc transversely through hub, first end Mounting Hole Thready Qty Per Inch (tpi): 56 transversely through hub, first end Mounting Hole Thread Size: 0.086 inches transversely through hub, first end Mounting Hole Type And Quantity: 1 plain transversely through hub, first end **Outside Diameter:** 0.372 inches Nominallength: 0.260 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.160 inches first end Face Width: 0.100 inches **Bore Diameter:** 0.125 inches both ends Hub Style Designator: Pinned first end **Hub Diameter:** 0.280 inches first end Mounting Hole Diameter: 0.040 inches transversely through hub, first end **Special Features:** Unthreaded hole 90 degrees from threaded hole Material:

Copper alloy 544

# NSN 3020-00-517-0834

Spur Gear - Page 2 of 2



#### Material Specification:

Astm b139, 4st, grade b2 assn standard single material response

#### Style Designator:

Protruding hub

Shelf Life:

N/a

### Unit Of Measure:

--

## Demilitarization:

No

Fiig:

A27300