## NSN 3020-00-517-0964

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-517-0964

Body Style:
Plain, with lightening holes
Attachment Method:
Mounting hole
Pitch Diameter:
2.4583 inches
Teeth Quantity:
118
Bore Style:
W/counterbore both ends
Mounting Hole Thread Series Designator:
Unc transversely through hub, first end
Mounting Hole Thready Qty Per Inch (tpi):
40 transversely through hub, first end
Mounting Hole Thread Size:
0.112 inches transversely through hub, first end
Mounting Hole Type And Quantity:
1 plain transversely through hub, first end and 1 threaded transversely through hub, first end
Outside Diameter:
2.500 inches
Nominallength:
0.703 inches
Tooth Form:
Standard
Pressure Angle:
14.5000 degrees
Distance Between Body Face And Protruding Hub End:
0.043 inches second end
Face Width:
0.125 inches
Bore Diameter:
0.187 inches both ends
Counterbore Depth:
0.094 inches second end
Counterbore Diameter:
0.281 inches second end
Hub Style Designator:
Plain second end
Hub Diameter:
0.343 inches second end
End Length:

0.125 inches first end

## **NSN 3020-00-517-0964** Spur Gear - Page 2 of 2



End Diameter:
0.250 inches first end
First Step Length:
0.410 inches first end
First Step Diameter:
0.625 inches first end
Mounting Hole Diameter:
0.057 inches transversely through hub, first end
Special Features:
60 degrees chamfer from counterbore to bore
Material:
Steel comp 416 hub
Material Specification:
Qq-s-764 federal specification single material response hub
Surface Treatment:
Passivate hub
Style Designator:
Protruding hubs
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A27300