NSN 3020-00-517-0975

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-517-0975

Body Style:
Webbed, solid
Attachment Method:
Mounting hole
Pitch Diameter:
4.8750 inches
Teeth Quantity:
78
Bore Style:
Tapered w/keyway first end
Mounting Hole Thread Series Designator:
Unc axially through body, first end
Mounting Hole Thready Qty Per Inch (tpi):
16 axially through body, first end
Hardness Rating:
32.0 rockwell c and 36.0 rockwell c
Mounting Hole Thread Size:
0.375 inches axially through body, first end
Mounting Hole Type And Quantity:
3 threaded axially through body, first end
Outside Diameter:
4.921 inches
Nominallength:
1.125 inches
Tooth Form:
Standard
Pressure Angle:
14.5000 degrees
Distance Between Body Face And Protruding Hub End:
0.469 inches first end
Face Width:
0.500 inches
Keyway Width:
0.158 inches both ends
Distance From Bore Center To Keyway Bottom:
0.510 inches both ends
Taper Major Diameter:
0.926 inches first end
Hub Style Designator:
Plain both ends
Hub Diameter:

1.375 inches second end

NSN 3020-00-517-0975

Spur Gear - Page 2 of 2

No Fiig: A27300



Bolt Hole Circle Diameter:
2.250 inches axially through body, first end
Special Features:
45 degrees chamfer 3/16 in. Lg on first hub end, 45 degrees chamfer 1/32 in. Lg on second hub end
Material:
Steel comp 4340
Material Specification:
Fed standard 66 federal standard single material response
Surface Treatment:
Zinc
Style Designator:
Protruding hubs
Shelf Life:
N/a
Unit Of Measure:

Demilitarization: