NSN 3020-00-517-1513

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-517-1513

| Body Style: |
|---|
| Plain, solid |
| Pitch Diameter: |
| 0.7210 inches |
| Teeth Quantity: |
| 35 |
| Bore Style: |
| W/ keyway both ends |
| Hardness Rating: |
| 45.0 rockwell c and 50.0 rockwell c |
| Outside Diameter: |
| 0.752 inches |
| Nominallength: |
| 0.250 inches |
| Tooth Form: |
| Standard |
| Pressure Angle: |
| 20.0000 degrees |
| Distance Between Body Face And Protruding Hub End: |
| 0.125 inches first end |
| Face Width: |
| 0.125 inches |
| Bore Diameter: |
| 0.250 inches both ends |
| Keyway Width: |
| 0.064 inches both ends |
| Distance From Bore Center To Keyway Bottom: |
| 0.165 inches both ends |
| Hub Style Designator: |
| Plain first end |
| Hub Diameter: |
| 0.406 inches first end |
| Material: |
| Steel comp 4620 |
| Material Specification: |
| Fed standard 66 federal standard single material response |
| Style Designator: |
| Protruding hub |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

--

NSN 3020-00-517-1513

Spur Gear - Page 2 of 2



Demilitarization:

No

Fiig:

A27300