

View Online at <https://aerobasegroup.com/nsn/3020-00-517-1624>

**Groove Depth:**

0.688 inches

**Groove Width:**

Between 0.656 inches and 0.658 inches

**Outside Diameter:**

14.625 inches

**Overall Length:**

2.688 inches

**Keyway Width:**

Between 0.375 inches and 0.376 inches

**Bore Length:**

2.438 inches

**Distance From Center Of Bore To Bottom Of Keyway:**

Between 0.975 inches and 1.000 inches

**V Groove Angle In Deg:**

38.0

**Pitch Diameter:**

14.125 inches

**Taper Bore Major Diameter:**

Between 1.748 inches and 1.749 inches

**Taper Bore Minor Diameter:**

Between 1.697 inches and 1.698 inches

**Material And Location:**

Steel, mil-s-20166, type b, grade m

**Face Width:**

2.500 inches

**Design Form:**

Webbed

**Bore Type:**

Tapered

**Bearings:**

Not included

**Taper Major Diameter Location:**

Aa end

**Groove Quantity:**

3

**Counterbore Feature:**

Not included

**Keying Facility:**

Included

**Keying Facility Type:**

Tapered keyway

**Split Hub Feature:**

Not included

**Web/spoke Relationship To Face Centerline:**

Not offset

**Lightening Hole:**

Included

**Integral Cooling Vane:**

Not included

**Groove Shape:**

V

**Standard V-belt Section Designation For Which Designed:**

B

**Bore Feature:**

Included

**Keying Facility Largest Dimension Location:**

Aa end

**Hub End Outside Diameter And Location:**

2.875 inches aa end and 3.000 inches bb end

**Distance From Outside Flange/rim To Hub End And Location:**

0.188 inches aa end and 0.250 inches bb end

**Quantity:**

1

**Surface Treatment:**

Zinc

**Style Designator:**

Webbed or spoked

**Surface Treatment:**

Zinc plated

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

T353-a