

View Online at <https://aerobasegroup.com/nsn/3020-00-517-1624>

Groove Depth:

0.688 inches

Groove Width:

Between 0.656 inches and 0.658 inches

Outside Diameter:

14.625 inches

Overall Length:

2.688 inches

Keyway Width:

Between 0.375 inches and 0.376 inches

Bore Length:

2.438 inches

Distance From Center Of Bore To Bottom Of Keyway:

Between 0.975 inches and 1.000 inches

V Groove Angle In Deg:

38.0

Pitch Diameter:

14.125 inches

Taper Bore Major Diameter:

Between 1.748 inches and 1.749 inches

Taper Bore Minor Diameter:

Between 1.697 inches and 1.698 inches

Material And Location:

Steel, mil-s-20166, type b, grade m

Face Width:

2.500 inches

Design Form:

Webbed

Bore Type:

Tapered

Bearings:

Not included

Taper Major Diameter Location:

Aa end

Groove Quantity:

3

Counterbore Feature:

Not included

Keying Facility:

Included

Keying Facility Type:

Tapered keyway

Split Hub Feature:

Not included

Web/spoke Relationship To Face Centerline:

Not offset

Lightening Hole:

Included

Integral Cooling Vane:

Not included

Groove Shape:

V

Standard V-belt Section Designation For Which Designed:

B

Bore Feature:

Included

Keying Facility Largest Dimension Location:

Aa end

Hub End Outside Diameter And Location:

2.875 inches aa end and 3.000 inches bb end

Distance From Outside Flange/rim To Hub End And Location:

0.188 inches aa end and 0.250 inches bb end

Quantity:

1

Surface Treatment:

Zinc

Style Designator:

Webbed or spoked

Surface Treatment:

Zinc plated

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T353-a