

View Online at <https://aerobasegroup.com/nsn/3020-00-517-1631>

**Groove Depth:**

0.688 inches

**Groove Width:**

0.656 inches

**Outside Diameter:**

5.875 inches

**Overall Length:**

2.313 inches

**Keyway Width:**

Between 0.749 inches and 0.750 inches

**Thread Size:**

3/8-16 or 1/2-13

**Bore Diameter:**

Between 0.874 inches and 0.875 inches

**Bore Length:**

1.750 inches

**Distance From Center Of Bore To Bottom Of Keyway:**

2.081 inches

**V Groove Angle In Deg:**

38.0

**Pitch Diameter:**

5.500 inches

**Securing Hole Quantity:**

1 or 2

**Material And Location:**

Iron, cast

**Face Width:**

1.625 inches

**Design Form:**

Spoked

**Bore Type:**

Straight

**Bearings:**

Not included

**Groove Quantity:**

2

**Counterbore Feature:**

Not included

**Hole Location:**

One located on center line of keyway on spokes w/2-3/4 in. Centers

**Keying Facility:**

Included

**Keying Facility Type:**

Keyway

**Securing Method:**

Threaded hole

**Split Hub Feature:**

Not included

**Web/spoke Relationship To Face Centerline:**

Offset

**Lightening Hole:**

Not included

**Integral Cooling Vane:**

Not included

**Groove Shape:**

V

**Standard V-belt Section Designation For Which Designed:**

B

**Bore Feature:**

Included

**Securing Location:**

Aa end

**Hub End Outside Diameter And Location:**

1.500 inches both ends

**Distance From Outside Flange/rim To Hub End And Location:**

0.563 inches aa end and 0.438 inches bb end

**Quantity:**

1

**Style Designator:**

Webbed or spoked

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

T353-a