

View Online at <https://aerobasegroup.com/nsn/3020-00-517-1631>

Groove Depth:

0.688 inches

Groove Width:

0.656 inches

Outside Diameter:

5.875 inches

Overall Length:

2.313 inches

Keyway Width:

Between 0.749 inches and 0.750 inches

Thread Size:

3/8-16 or 1/2-13

Bore Diameter:

Between 0.874 inches and 0.875 inches

Bore Length:

1.750 inches

Distance From Center Of Bore To Bottom Of Keyway:

2.081 inches

V Groove Angle In Deg:

38.0

Pitch Diameter:

5.500 inches

Securing Hole Quantity:

1 or 2

Material And Location:

Iron, cast

Face Width:

1.625 inches

Design Form:

Spoked

Bore Type:

Straight

Bearings:

Not included

Groove Quantity:

2

Counterbore Feature:

Not included

Hole Location:

One located on center line of keyway on spokes w/2-3/4 in. Centers

Keying Facility:

Included

Keying Facility Type:

Keyway

Securing Method:

Threaded hole

Split Hub Feature:

Not included

Web/spoke Relationship To Face Centerline:

Offset

Lightening Hole:

Not included

Integral Cooling Vane:

Not included

Groove Shape:

V

Standard V-belt Section Designation For Which Designed:

B

Bore Feature:

Included

Securing Location:

Aa end

Hub End Outside Diameter And Location:

1.500 inches both ends

Distance From Outside Flange/rim To Hub End And Location:

0.563 inches aa end and 0.438 inches bb end

Quantity:

1

Style Designator:

Webbed or spoked

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T353-a