

View Online at <https://aerobasegroup.com/nsn/3020-00-517-1632>

Groove Depth:

0.687 inches

Groove Width:

Between 0.654 inches and 0.658 inches

Outside Diameter:

6.313 inches

Overall Length:

2.250 inches

Keyway Width:

Between 0.1863 inches and 0.1880 inches

Thread Size:

3/8 - 16

Bore Diameter:

Between 0.873 inches and 0.874 inches

Bore Length:

1.813 inches

Distance From Center Of Bore To Bottom Of Keyway:

0.576 inches

V Groove Angle In Deg:

38.0

Pitch Diameter:

5.938 inches

Securing Hole Quantity:

1

Material And Location:

Iron, cast

Face Width:

1.625 inches

Design Form:

Webbed

Bore Type:

Straight

Bearings:

Not included

Groove Quantity:

2

Counterbore Feature:

Not included

Hole Location:

Located 180 degrees from keyway

Keying Facility:

Included

Keying Facility Type:

Keyway

Securing Method:

Threaded hole

Split Hub Feature:

Not included

Web/spoke Relationship To Face Centerline:

Not offset

Lightening Hole:

Included

Integral Cooling Vane:

Not included

Groove Shape:

V

Standard V-belt Section Designation For Which Designed:

B

Bore Feature:

Included

Securing Location:

Aa end

Hub End Outside Diameter And Location:

1.500 inches both ends

Distance From Outside Flange/rim To Hub End And Location:

0.625 inches aa end and 0.438 inches bb end

Quantity:

1

Style Designator:

Webbed or spoked

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T353-a