

View Online at <https://aerobasegroup.com/nsn/3020-00-517-1632>

**Groove Depth:**

0.687 inches

**Groove Width:**

Between 0.654 inches and 0.658 inches

**Outside Diameter:**

6.313 inches

**Overall Length:**

2.250 inches

**Keyway Width:**

Between 0.1863 inches and 0.1880 inches

**Thread Size:**

3/8 - 16

**Bore Diameter:**

Between 0.873 inches and 0.874 inches

**Bore Length:**

1.813 inches

**Distance From Center Of Bore To Bottom Of Keyway:**

0.576 inches

**V Groove Angle In Deg:**

38.0

**Pitch Diameter:**

5.938 inches

**Securing Hole Quantity:**

1

**Material And Location:**

Iron, cast

**Face Width:**

1.625 inches

**Design Form:**

Webbed

**Bore Type:**

Straight

**Bearings:**

Not included

**Groove Quantity:**

2

**Counterbore Feature:**

Not included

**Hole Location:**

Located 180 degrees from keyway

**Keying Facility:**

Included

**Keying Facility Type:**

Keyway

**Securing Method:**

Threaded hole

**Split Hub Feature:**

Not included

**Web/spoke Relationship To Face Centerline:**

Not offset

**Lightening Hole:**

Included

**Integral Cooling Vane:**

Not included

**Groove Shape:**

V

**Standard V-belt Section Designation For Which Designed:**

B

**Bore Feature:**

Included

**Securing Location:**

Aa end

**Hub End Outside Diameter And Location:**

1.500 inches both ends

**Distance From Outside Flange/rim To Hub End And Location:**

0.625 inches aa end and 0.438 inches bb end

**Quantity:**

1

**Style Designator:**

Webbed or spoked

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

T353-a