

View Online at <https://aerobasegroup.com/nsn/3020-00-517-1637>

**Groove Depth:**

0.625 inches

**Groove Width:**

0.656 inches

**Outside Diameter:**

5.375 inches

**Overall Length:**

1.156 inches

**Keyway Width:**

Between 0.156 inches and 0.157 inches

**Bore Diameter:**

Between 0.156 inches and 0.157 inches

**Bore Length:**

1.156 inches

**Distance From Center Of Bore To Bottom Of Keyway:**

Between 0.5735 inches and 0.5790 inches

**V Groove Angle In Deg:**

38.0

**Pitch Diameter:**

4.625 inches

**Material And Location:**

Iron, cast

**Face Width:**

0.875 inches

**Design Form:**

Webbed

**Bore Type:**

Straight

**Bearings:**

Not included

**Groove Quantity:**

1

**Counterbore Feature:**

Not included

**Keying Facility:**

Included

**Keying Facility Type:**

Keyway

**Split Hub Feature:**

Not included

**Web/spoke Relationship To Face Centerline:**

Offset

**Lightening Hole:**

Included

**Integral Cooling Vane:**

Not included

**Groove Shape:**

V

**Standard V-belt Section Designation For Which Designed:**

B

**Bore Feature:**

Included

**Protruding Hub Characteristic:**

Stepped

**Hub End Outside Diameter And Location:**

1.375 inches aa end and 1.2995 inches bb end and 1.3005 inches bb end

**Distance From Outside Flange/rim To Hub End And Location:**

0.219 inches aa end and 0.063 inches bb end

**First Step Face Largest Diameter And Location:**

1.625 inches both ends

**First Step Length And Location:**

0.406 inches both ends

**Quantity:**

1

**Style Designator:**

Webbed or spoked

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

T353-a