## NSN 3020-00-517-1760

Groove Pulley - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-517-1760 **Groove Depth:** 0.563 inches **Groove Width:** 0.450 inches **Outside Diameter:** 3.813 inches **Overall Length:** 2.188 inches **Keyway Width:** 0.188 inches **Thread Size:** 1/4 - 20 **Bore Diameter:** Between 0.625 inches and 0.630 inches Bore Length: 2.125 inches **Distance From Center Of Bore To Bottom Of Keyway:** 0.406 inches V Groove Angle In Deg: 38.0 Pitch Diameter: 3.500 inches **Securing Hole Quantity: Furnished Items And Quantity:** Key, 1; setscrews, 2 **Material And Location:** Iron, n, 46-i-5, class a **Face Width:** 0.750 inches **Design Form:** Webbed **Bore Type:** Straight Bearings: Not included **Groove Quantity:** 1

Counterbore Feature:

Not included

**Hole Location:** 

Located on top of keyway

## NSN 3020-00-517-1760

Groove Pulley - Page 2 of 2



Kaving English
Keying Facility: Included
Keying Facility Type:
Keyway
Securing Method:
Threaded hole
Split Hub Feature:
Not included
Web/spoke Relationship To Face Centerline:
Not offset
Lightening Hole:
Not included
Integral Cooling Vane:
Not included
Groove Shape:
V
Bore Feature:
Included
Protruding Hub Characteristic:
Stepped
Securing Location:
Both ends
Hub End Outside Diameter And Location:
1.250 inches both ends
Distance From Outside Flange/rim To Hub End And Location:
1.438 inches both ends
First Step Face Largest Diameter And Location:
2.031 inches both ends
First Step Length And Location:
0.063 inches both ends
Special Features:
1 hole located in bottom of pulley groove
Quantity:
1
Style Designator:
Webbed or spoked
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No
Fiig:

T353-a