

View Online at <https://aerobasegroup.com/nsn/3020-00-517-1760>

Groove Depth:

0.563 inches

Groove Width:

0.450 inches

Outside Diameter:

3.813 inches

Overall Length:

2.188 inches

Keyway Width:

0.188 inches

Thread Size:

1/4 - 20

Bore Diameter:

Between 0.625 inches and 0.630 inches

Bore Length:

2.125 inches

Distance From Center Of Bore To Bottom Of Keyway:

0.406 inches

V Groove Angle In Deg:

38.0

Pitch Diameter:

3.500 inches

Securing Hole Quantity:

2

Furnished Items And Quantity:

Key, 1; setscrews, 2

Material And Location:

Iron, n, 46-i-5, class a

Face Width:

0.750 inches

Design Form:

Webbed

Bore Type:

Straight

Bearings:

Not included

Groove Quantity:

1

Counterbore Feature:

Not included

Hole Location:

Located on top of keyway

Keying Facility:

Included

Keying Facility Type:

Keyway

Securing Method:

Threaded hole

Split Hub Feature:

Not included

Web/spoke Relationship To Face Centerline:

Not offset

Lightening Hole:

Not included

Integral Cooling Vane:

Not included

Groove Shape:

V

Bore Feature:

Included

Protruding Hub Characteristic:

Stepped

Securing Location:

Both ends

Hub End Outside Diameter And Location:

1.250 inches both ends

Distance From Outside Flange/rim To Hub End And Location:

1.438 inches both ends

First Step Face Largest Diameter And Location:

2.031 inches both ends

First Step Length And Location:

0.063 inches both ends

Special Features:

1 hole located in bottom of pulley groove

Quantity:

1

Style Designator:

Webbed or spoked

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T353-a