NSN 3020-00-517-2398

Sprocket Wheel - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-517-2398

Outside Diameter:

5.082 inches

Overall Length:

1.125 inches

Keyway Width:

0.250 inches

Thread Size:

5/16-18

Bore Diameter:

1.250 inches

Bore Length:

1.125 inches

Distance From Center Of Bore To Bottom Of Keyway:

0.875 inches

Pitch Diameter:

4.788 inches

Securing Hole Quantity:

1

Face Width:

0.343 inches

Guide:

Not included

Design Form:

Plain

Bore Type:

Straight

Counterbore Feature:

Not included

Hole Location:

Located on top of key

Keying Facility:

Included

Keying Facility Type:

Keyway

Securing Method:

Threaded hole

Lightening Hole:

Not included

Protruding Hub Characteristic:

Plain

Securing Location:

Aa end

NSN 3020-00-517-2398 Sprocket Wheel - Page 2 of 2



	/film Size For Which Designed:
Roller chai	
	ain Pitch Type For Which Designed:
Single pitcl	
	v Quantity:
1	
	ntity Per Row:
24	
Asa Stand	lard Chain Number:
50	
	Rating Test Method:
Not rated	
Bore Bear	
Not include	
	nal Keyway:
Not include	
Tooth Pito	
0.625 inch	
Hub End C	Dutside Diameter And Location:
3.500 inch	
Distance F	From Outside Flange/rim To Hub End And Location:
0.782 inch	es aa end
Material:	
Steel	
Material:	
Steel	
Quantity:	
1	
Style Desi	gnator:
Plain	
Shelf Life:	
N/a	
Unit Of Me	easure:
Demilitaria	zation:
No	
Fiig:	
Т353-с	