NSN 3020-00-517-2421

Sprocket Wheel - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-517-2421

Outside Diameter:
13.185 inches
Overall Length:
1.188 inches
Keyway Width:
0.312 inches
Key Width:
0.250 inches
Bore Diameter:
Between 1.188 inches and 1.1886 inches
Bore Length:
1.188 inches
Distance From Center Of Bore To Bottom Of Keyway:
0.844 inches
Pitch Diameter:
12.895 inches
Face Width:
0.284 inches
Guide:
Not included
Design Form:
Plain
Bore Type:
Straight
Counterbore Feature:
Not included
Keying Facility:
Included
Keying Facility Type:
Keyway
Lightening Hole:
Included
Belt/chain/film Size For Which Designed:
Roller chain
Roller Chain Pitch Type For Which Designed:
Single pitch
Teeth Row Quantity:
1
Teeth Quantity Per Row:
81
Asa Standard Chain Number:

40

NSN 3020-00-517-2421 Sprocket Wheel - Page 2 of 2



Hardness Rating Test Method:
Not rated
Bore Bearing:
Not included
Hub External Keyway:
Not included
Tooth Pitch:
0.500 inches
Hub End Outside Diameter And Location:
2.000 inches aa end and 1.875 inches bb end
Distance From Outside Flange/rim To Hub End And Location:
0.5455 inches aa end and 0.296 inches bb end
Material:
Steel, mil-s-16113, grade m and steel, mil-s-20166, grade m
Material:
Steel uns k11801 or steel uns k11802 and steel comp 1022
Material Specification:
Mil-s-16113, grade m military specification 1st material response and mil-s-20166, grade m military specification 2nd material response
Quantity:
1
Style Designator:
Plain
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
T353-c
Mil-std (military Standard):
Mil-s-16113 spec.