NSN 3020-00-517-2422

Sprocket Wheel - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-517-2422 **Outside Diameter:** 5.675 inches **Overall Length:** 1.750 inches **Keyway Width:** Between 0.373 inches and 0.375 inches **Bore Diameter:** Between 3.620 inches and 3.630 inches Bore Length: 1.750 inches Distance From Center Of Bore To Bottom Of Keyway: 1.9531 inches Pitch Diameter: 5.270 inches **Face Width:** 1.341 inches **Guide:** Not included **Design Form:** Plain **Bore Type:** Straight **Counterbore Feature:** Not included **Keying Facility:** Included **Keying Facility Type:** Keyway **Securing Method:** Any acceptable **Lightening Hole:** Not included **Protruding Hub Characteristic:** Plain Belt/chain/film Size For Which Designed: Roller chain **Roller Chain Pitch Type For Which Designed:** Single pitch **Teeth Row Quantity:**

2

Center To Center Distance Between Teeth Rows:

0.897 inches

NSN 3020-00-517-2422 Sprocket Wheel - Page 2 of 2



Teeth Quantity Per Row:
22
Asa Standard Chain Number:
60
Hardness Rating Test Method:
Rockwell
Teeth Hardness Rating:
Between 35.0 rockwell c and 50.0 rockwell c
Bore Bearing:
Not included
Hub External Keyway:
Not included
Tooth Pitch:
0.750 inches
Hub End Outside Diameter And Location:
4.375 inches both ends
Distance From Outside Flange/rim To Hub End And Location:
0.204 inches both ends
Special Features:
0.125 in. By 45 degrees chamfer on both ends of bore
Material:
Steel, sae 1113
Material:
Steel comp 1213
Material Specification:
Sae 1113 assn standard single material response
Quantity:
1
Style Designator:
Plain
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
T353-c