## NSN 3020-00-517-2424

Sprocket Wheel - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-517-2424

**Outside Diameter:** 4.420 inches **Overall Length:** 1.438 inches **Keyway Width:** Between 0.251 inches and 0.253 inches **Bore Diameter:** Between 1.2430 inches and 1.2480 inches **Bore Length:** 1.438 inches Distance From Center Of Bore To Bottom Of Keyway: Between 0.6446 inches and 0.7494 inches Pitch Diameter: 4.148 inches **Face Width:** 0.838 inches Guide: Not included **Design Form:** Plain **Bore Type:** Straight **Metallic Hardness Rating And Location:** 35.0 rockwell c body and 45.0 rockwell c body **Counterbore Feature:** Not included **Keying Facility:** Included **Keying Facility Type:** Keyway **Lightening Hole:** Not included **Protruding Hub Characteristic:** Plain Belt/chain/film Size For Which Designed: Roller chain **Roller Chain Pitch Type For Which Designed:** Single pitch **Teeth Row Quantity:** 

2

**Center To Center Distance Between Teeth Rows:** 

0.563 inches

## **NSN 3020-00-517-2424** Sprocket Wheel - Page 2 of 2



Teeth Quantity Per Row:
26
Asa Standard Chain Number:
40
Hardness Rating Test Method:
Rockwell
Teeth Hardness Rating:
Between 35.0 rockwell c and 45.0 rockwell c
Bore Bearing:
Not included
Hub External Keyway:
Not included
Tooth Pitch:
0.500 inches
Hub End Outside Diameter And Location:
3.500 inches both ends
Distance From Outside Flange/rim To Hub End And Location:
0.29975 inches both ends
Special Features:
Hub chamfered one end 1/8 in by 45 deg; oil hole 1/8 in. Diameter located between center row of teeth through to bore
Material:
Steel, aisi b1113
Material:
Steel comp 1213
Material Specification:
Aisi b1113 assn standard single material response
Quantity:
1
Style Designator:
Plain
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
T353-c