NSN 3020-00-517-2425

Sprocket Wheel - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-517-2425

Counterbore Diameter:
3.1491 inches and 3.1491 inches
Counterbore Depth:
Between 0.614 inches and 0.624 inches and 0.7047 inches and 0.7147 inches
Outside Diameter:
5.675 inches
Overall Length:
2.344 inches
Bolt Circle Diameter:
3.750 inches
Thread Size:
5/16-24
Bore Diameter:
2.875 inches
Bore Length:
2.344 inches
Pitch Diameter:
5.270 inches
Securing Hole Quantity:
4
Face Width:
1.341 inches
Design Form:
Plain
Bore Type:
Straight
Counterbore Feature:
Included
Counterbore Location:
Both ends
Hole Location:
Located 90 degrees apart, horizontal to bore on 3-3/4 in. Bolt circle
Keying Facility:
Not included
Securing Method:
Threaded hole
Lightening Hole:
Not included
Securing Location:

Aa end

Belt/chain/film Size For Which Designed:

Roller chain

NSN 3020-00-517-2425 Sprocket Wheel - Page 2 of 2



Roller Chain Pitch Type For Which Designed:
Single pitch
Teeth Row Quantity:
2
Center To Center Distance Between Teeth Rows:
0.897 inches
Teeth Quantity Per Row:
22
Asa Standard Chain Number:
60
Hardness Rating Test Method:
Rockwell
Teeth Hardness Rating:
Between 35.0 rockwell c and 50.0 rockwell c
Bore Bearing:
Not included
Hub External Keyway:
Not included
Tooth Pitch:
0.750 inches
Hub End Outside Diameter And Location:
4.375 inches both ends
Distance From Outside Flange/rim To Hub End And Location:
0.673 inches aa end and 0.324 inches bb end and 0.334 inches bb end
Special Features:
0.062 in. By 45 degrees chamfer both ends of bore; 0.031 in. Deep by 0.125 in. W relief at bottom of counterbore both ends
Material:
Steel, sae 1113
Material:
Steel comp 1213
Material Specification:
Sae 1113 assn standard single material response
Style Designator:
Plain
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
Т353-с