NSN 3020-00-517-2430

Sprocket Wheel - Page 1 of 2

Outside Diameter:



View Online at https://aerobasegroup.com/nsn/3020-00-517-2430

Between 6.318 inches and 6.321 inches
Bore Diameter:
Between 1.620 inches and 1.623 inches
Bore Length:
2.219 inches
Pitch Diameter:
5.979 inches
Face Width:
Between 2.443 inches and 2.445 inches
Guide:
Not included
Design Form:
Webbed
Bore Type:
Straight
Metallic Hardness Rating And Location:
16.0 rockwell c body
Counterbore Feature:
Not included
Lubrication Mode:
Visible means
Keying Facility:
Not included
Lightening Hole:
Not included
Belt/chain/film Size For Which Designed:
Roller chain
Roller Chain Pitch Type For Which Designed:
Single pitch
Teeth Row Quantity:
4
Center To Center Distance Between Teeth Rows:
0.707 inches
Teeth Quantity Per Row:
30
Asa Standard Chain Number:
50-4
Hardness Rating Test Method:
Rockwell

Teeth Hardness Rating:

Between 10.0 rockwell c and 16.0 rockwell c

NSN 3020-00-517-2430 Sprocket Wheel - Page 2 of 2



Bore Bearing:
Not included
Hub External Keyway:
Not included
Tooth Pitch:
0.625 inches
Hub End Outside Diameter And Location:
2.750 inches both ends
Distance From Outside Flange/rim To Hub End And Location:
0.113 inches both ends and 0.111 inches both ends
Material:
Steel, mil-s-15464, class 3
Material:
Steel, mil-s-15464, class 3
Style Designator:
Webbed or spoked
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
T353-c