NSN 3020-00-517-2435

Sprocket Wheel - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-517-2435

Outside Diameter:
Between 6.718 inches and 6.721 inches
Overall Length:
Between 3.159 inches and 3.163 inches
Keyway Width:
0.375 inches
Bore Diameter:
Between 1.6245 inches and 1.6255 inches
Bore Length:
Between 3.159 inches and 3.163 inches
Distance From Center Of Bore To Bottom Of Keyway:
1.000 inches
Pitch Diameter:
6.376 inches
Face Width:
Between 2.443 inches and 2.445 inches
Design Form:
Webbed
Bore Type:
Straight
Counterbore Feature:
Not included
Keying Facility:
Included
Keying Facility Type:
Keyway
Lightening Hole:
Not included
Belt/chain/film Size For Which Designed:
Roller chain
Roller Chain Pitch Type For Which Designed:
Single pitch
Teeth Row Quantity:
4
Center To Center Distance Between Teeth Rows:
0.707 inches
Teeth Quantity Per Row:
32
Asa Standard Chain Number:
50-4
Hardness Rating Test Method:

Not rated

NSN 3020-00-517-2435 Sprocket Wheel - Page 2 of 2



Bore Bearing:
Not included
Tooth Pitch:
0.625 inches
Hub End Outside Diameter And Location:
2.500 inches aa end and 2.625 inches bb end
Distance From Outside Flange/rim To Hub End And Location:
0.717 inches aa end
Material:
Steel, mil-s-890, alloy no. 3
Material:
Steel
Material Specification:
Mil-s-890, alloy no. 3 military specification single material response
Quantity:
1
Style Designator:
Webbed or spoked
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
Т353-с
Mil-std (military Standard):
Mil-s-890 spec.