## NSN 3020-00-517-2880

Helical Gear - Page 1 of 2

**Body Style:** Plain, solid

Mounting hole

Pitch Diameter:

**Attachment Method:** 



View Online at https://aerobasegroup.com/nsn/3020-00-517-2880

1.6250 inches		
Teeth Quantity:		
12		
Bore Style:		
W/ keyway both ends		
Mounting Hole Thread Series Designator:		
Unf axially through body, first end		
Mounting Hole Thread Size:		
0.1900 inches axially through body, first end		
Mounting Hole Type And Quantity:		
2 threaded axially through body, first end		
Outside Diameter:		
1.8745 inches		
Teeth Type:		
Single helix		
Tooth Form:		
Standard		
Tooth Direction:		
Right		
Dunanas Assaulas		
Pressure Angle:		
20.0000 degrees		
20.0000 degrees		
20.0000 degrees Helix Angle:		
20.0000 degrees  Helix Angle: 10.0000 degrees		
20.0000 degrees  Helix Angle: 10.0000 degrees  Face Width:		
20.0000 degrees  Helix Angle: 10.0000 degrees  Face Width: 2.4999 inches		
20.0000 degrees  Helix Angle: 10.0000 degrees  Face Width: 2.4999 inches  Bore Diameter:		
20.0000 degrees  Helix Angle: 10.0000 degrees  Face Width: 2.4999 inches  Bore Diameter: 0.7507 inches both ends		
20.0000 degrees  Helix Angle: 10.0000 degrees  Face Width: 2.4999 inches  Bore Diameter: 0.7507 inches both ends  Keyway Width:		
20.0000 degrees  Helix Angle: 10.0000 degrees  Face Width: 2.4999 inches  Bore Diameter: 0.7507 inches both ends  Keyway Width: 0.1875 inches both ends		
20.0000 degrees  Helix Angle: 10.0000 degrees  Face Width: 2.4999 inches  Bore Diameter: 0.7507 inches both ends  Keyway Width: 0.1875 inches both ends  Distance From Bore Center To Keyway Bottom:		
20.0000 degrees  Helix Angle: 10.0000 degrees  Face Width: 2.4999 inches  Bore Diameter: 0.7507 inches both ends  Keyway Width: 0.1875 inches both ends  Distance From Bore Center To Keyway Bottom: 0.4645 inches both ends		
20.0000 degrees  Helix Angle: 10.0000 degrees  Face Width: 2.4999 inches  Bore Diameter: 0.7507 inches both ends  Keyway Width: 0.1875 inches both ends  Distance From Bore Center To Keyway Bottom: 0.4645 inches both ends  Bolt Hole Circle Diameter:		
20.0000 degrees  Helix Angle: 10.0000 degrees  Face Width: 2.4999 inches  Bore Diameter: 0.7507 inches both ends  Keyway Width: 0.1875 inches both ends  Distance From Bore Center To Keyway Bottom: 0.4645 inches both ends  Bolt Hole Circle Diameter: 1.062 inches axially through body, first end		
20.0000 degrees  Helix Angle: 10.0000 degrees  Face Width: 2.4999 inches  Bore Diameter: 0.7507 inches both ends  Keyway Width: 0.1875 inches both ends  Distance From Bore Center To Keyway Bottom: 0.4645 inches both ends  Bolt Hole Circle Diameter: 1.062 inches axially through body, first end  Material:		
20.0000 degrees  Helix Angle: 10.0000 degrees  Face Width: 2.4999 inches  Bore Diameter: 0.7507 inches both ends  Keyway Width: 0.1875 inches both ends  Distance From Bore Center To Keyway Bottom: 0.4645 inches both ends  Bolt Hole Circle Diameter: 1.062 inches axially through body, first end  Material: Copper alloy		

## NSN 3020-00-517-2880

Helical Gear - Page 2 of 2



	Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A27300