NSN 3020-00-517-2925

Helical Gear - Page 1 of 2

Body Style:

Webbed, offset, solid



View Online at https://aerobasegroup.com/nsn/3020-00-517-2925

| Pitch Diameter: |
|--|
| 18.1500 inches |
| Teeth Quantity: |
| 121 |
| Bore Style: |
| Tapered w/keyway first end |
| Features Provided: |
| Tapered keyway |
| Outside Diameter: |
| 18.4360 inches |
| Teeth Type: |
| Single helix |
| Tooth Form: |
| Standard |
| Tooth Direction: |
| Left |
| Pressure Angle: |
| 14.5000 degrees |
| Helix Angle: |
| 17.7498 degrees |
| Distance Between Body Face And Protruding Hub End: |
| 1.313 inches first end |
| Distance Between Body Face And Recessed Hub End: |
| 1.1875 inches second end |
| Face Width: |
| 2.9999 inches |
| Keyway Width: |
| 0.6260 inches first end |
| Distance From Bore Center To Keyway Bottom: |
| 1.4453 inches first end |
| Taper Major Diameter: |
| 2.2505 inches first end |
| Hub Style Designator: |
| Plain both ends |
| Hub Diameter: |
| 5.0000 inches both ends |
| Material: |
| Steel |
| Material Specification: |
| Mil-s-890, alloy no. 1 military specification single material response |
| |

NSN 3020-00-517-2925

Helical Gear - Page 2 of 2



| Style Designator: |
|--------------------------------------|
| One protruding hub, one recessed hub |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |

Mil-std (military Standard):

Mil-s-890 spec.

A27300