NSN 3020-00-517-3176

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-517-3176

De de Oteder
Body Style: Webbed, solid
Attachment Method:
Mounting hole
Pitch Diameter:
10.2500 inches
Teeth Quantity: 41
Bore Style:
W/counterbore counterbore, first end
Mounting Hole Thread Series Designator:
Unf transversely through hub, first end
Hardness Rating:
24.0 rockwell c and 29.0 rockwell c
Mounting Hole Thread Size: 0.500 inches transversely through hub, first end
Mounting Hole Type And Quantity: 3 plain transversely through hub, first end and 3 threaded transversely through hub, first end
Outside Diameter:
10.722 inches
Tooth Form:
Standard
Pressure Angle:
20.0000 degrees
Face Width:
3.000 inches
Bore Diameter:
3.626 inches counterbore, first end
Counterbore Depth:
0.250 inches counterbore, first end
Counterbore Diameter:
6.501 inches counterbore, first end
Hub Style Designator: Plain both ends
Hub Diameter:
7.000 inches first end
Mounting Hole Diameter:
0.500 inches transversely through hub, first end
Special Features:
Unthd holes 0.6875 in. Deep in. Deep, thd holes 1.125 in. Deep, unthd and thd holes alternate 60 degrees apart
Material:
Steel comp 8642h

NSN 3020-00-517-3176

Spur Gear - Page 2 of 2



Material Specification	V	late	rial	Spe	cific	cation	۱:
------------------------	---	------	------	-----	-------	--------	----

Fed-std-66 federal standard single material response

Style Designator:

Flush hub

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A27300