NSN 3020-00-517-3188

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-517-3188

Body Style:

Webbed, with lightening holes

Attachment Method:

Mounting hole

Pitch Diameter:

8.3333 inches

Teeth Quantity:

50

Bore Style:

W/ keyway both ends

Mounting Hole Thread Series Designator:

Unc transversely through hub, first end

Mounting Hole Thready Qty Per Inch (tpi):

13 transversely through hub, first end

Hardness Rating:

59.0 rockwell c and 62.0 rockwell c

Mounting Hole Thread Size:

0.500 inches transversely through hub, first end

Mounting Hole Type And Quantity:

2 threaded transversely through hub, first end

Outside Diameter:

8.666 inches

Nominallength:

3.000 inches

Tooth Form:

Standard

Pressure Angle:

20.0000 degrees

Distance Between Body Face And Protruding Hub End:

0.500 inches both ends

Face Width:

2.000 inches

Bore Diameter:

2.874 inches both ends

Keyway Width:

0.500 inches both ends

Distance From Bore Center To Keyway Bottom:

1.686 inches both ends

Hub Style Designator:

Plain both ends

Hub Diameter:

3.875 inches second end

NSN 3020-00-517-3188

Spur Gear - Page 2 of 2



Material:

Steel comp 4615 and steel comp e4340h

Material Specification:

66, aisi/sae 4615, e4340h federal standard single material response

Style Designator:

Protruding hubs

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A27300