
## NSN 3020-00-517-3222

Helical Gear - Page 1 of 2





**Body Style:** Plain, solid **Attachment Method:** Mounting hole **Pitch Diameter:** 2.6040 inches **Teeth Quantity:** 123 **Bore Style:** Plain both ends Mounting Hole Thread Series Designator: Unc transversely through hub, first end Mounting Hole Thready Qty Per Inch (tpi): 40 transversely through hub, first end Mounting Hole Thread Size: 0.1120 inches transversely through hub, first end Mounting Hole Type And Quantity: 1 threaded transversely through hub, first end **Outside Diameter:** 2.6460 inches **Teeth Type:** Single helix **Tooth Form:** Standard **Tooth Direction:** Right **Pressure Angle:** 14.5000 degrees **Helix Angle:** 3.5498 degrees **Distance Between Body Face And Protruding Hub End:** 0.281 inches first end Face Width: 0.188 inches **Bore Diameter:** 2.1869 inches both ends Hub Style Designator: 1 step first end End Length: 0.0310 inches first end End Diameter: 0.3750 inches first end

# NSN 3020-00-517-3222

Helical Gear - Page 2 of 2



## First Step Length:

0.2500 inches first end

#### First Step Diameter:

0.5000 inches first end

#### Material:

Copper alloy

## Material Specification:

Naval, mil-b-994 military specification single material response

#### Style Designator:

Protruding hub

Shelf Life:

N/a

## Unit Of Measure:

---

#### Demilitarization:

No

## Fiig:

A27300

## Mil-std (military Standard):

Mil-b-994 spec.