## NSN 3020-00-517-3848

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-517-3848

Body Style:
Plain, solid
Attachment Method:
Mounting hole
Pitch Diameter:
1.4000 inches
Teeth Quantity:
96
Bore Style:
W/ keyway both ends
Mounting Hole Thread Series Designator:
Unc axially through body, first end
Mounting Hole Thready Qty Per Inch (tpi):
32 axially through body, first end
Mounting Hole Thread Size:
0.164 inches axially through body, first end
Outside Diameter:
1.500 inches
Nominallength:
0.688 inches
Tooth Form:
Standard
Pressure Angle:
14.5000 degrees
Distance Between Body Face And Protruding Hub End:
0.313 inches first end
Face Width:
0.375 inches
Bore Diameter:
0.750 inches both ends
Keyway Width:
0.126 inches both ends
Distance From Bore Center To Keyway Bottom:
0.438 inches both ends
Hub Style Designator:
Pinned first end
Hub Diameter:
1.188 inches first end
Mounting Hole Diameter:
0.166 inches transversely through hub, first end

**Special Features:** 

Thd hole 180 degrees from keyway; unthd hole 90 degrees from keyway

## **NSN 3020-00-517-3848** Spur Gear - Page 2 of 2

Fiig: A27300



Material:
Steel comp 416
Material Specification:
Qq-s-763, class416 federal specification single material response
Style Designator:
Protruding hub
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No