NSN 3020-00-517-7334

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-517-7334 **Body Style:** Webbed, offset, solid **Attachment Method:** Mounting hole Pitch Diameter: 4.2000 inches **Teeth Quantity:** 42 **Bore Style:** W/ keyway both ends **Mounting Hole Thread Series Designator:** Unc axially through body, first end **Hardness Rating:** 36.0 rockwell c and 42.0 rockwell c **Mounting Hole Thread Size:** 0.375 inches axially through body, first end **Mounting Hole Type And Quantity:** 2 threaded axially through body, first end **Outside Diameter:** 4.383 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.702 inches first end Distance Between Body Face And Recessed Hub End: 0.155 inches second end **Face Width:** 0.445 inches **Bore Diameter:** 0.688 inches both ends **Keyway Width:** 0.125 inches both ends **Distance From Bore Center To Keyway Bottom:** 0.4112 inches both ends **Hub Style Designator:** Plain both ends **Hub Diameter:** 1.250 inches both ends

Material:

Steel comp 4340

NSN 3020-00-517-7334

Spur Gear - Page 2 of 2



	Materia	al Sp	ecific	ation:
--	---------	-------	--------	--------

Fed-std-66 federal standard single material response

Style Designator:

One protruding hub, one recessed hub

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A27300