NSN 3020-00-523-3295

Spur Gear - Page 1 of 2

Body Style:



View Online at https://aerobasegroup.com/nsn/3020-00-523-3295

| Plain, solid | | | | | |
|--|--|--|--|--|--|
| Spline Quantity: | | | | | |
| 32 both ends | | | | | |
| Attachment Method: | | | | | |
| Mounting hole | | | | | |
| Pitch Diameter: | | | | | |
| 4.6627 inches | | | | | |
| Teeth Quantity: | | | | | |
| 45 | | | | | |
| Bore Style: | | | | | |
| Involute spline both ends | | | | | |
| Spline Pitch Diameter: | | | | | |
| 2.0000 inches both ends | | | | | |
| Hardness Rating: | | | | | |
| 81.0 rockwell a and 85.0 rockwell a teeth | | | | | |
| Mounting Hole Type And Quantity: | | | | | |
| 2 plain axially through hub, first end | | | | | |
| Outside Diameter: | | | | | |
| 4.847 inches | | | | | |
| Tooth Form: | | | | | |
| Standard | | | | | |
| Pressure Angle: | | | | | |
| 22.5000 degrees | | | | | |
| Distance Between Body Face And Protruding Hub End: | | | | | |
| 0.160 inches second end | | | | | |
| Face Width: | | | | | |
| 0.200 inches | | | | | |
| Bore Diameter: | | | | | |
| 2.121 inches both ends | | | | | |
| Hub Style Designator: | | | | | |
| Plain both ends | | | | | |
| Mounting Hole Diameter: | | | | | |
| 0.156 inches axially through hub, first end | | | | | |
| Bolt Hole Circle Diameter: | | | | | |
| 2.3500 inches axially through hub, first end | | | | | |
| Material: | | | | | |
| Steel comp e9310 | | | | | |
| Material Specification: | | | | | |
| Ams 6260 assn standard single material response | | | | | |
| Style Designator: | | | | | |
| Cone shape body, protruding hub | | | | | |

NSN 3020-00-523-3295

Spur Gear - Page 2 of 2



| C | ha | Ιf | 1 | ife | |
|---|-----|----|---|-------|--|
| • | ııe | | _ | .II C | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A27300