NSN 3020-00-526-9608

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-526-9608

Body Style:
Plain, solid
Attachment Method:
Clamp
Pitch Diameter:
1.1979 inches
Teeth Quantity:
115
Bore Style:
Plain both ends
Outside Diameter:
1.217 inches
Nominallength:
0.300 inches
Tooth Form:
Standard
Pressure Angle:
20.0000 degrees
Distance Between Body Face And Protruding Hub End:
0.250 inches first end
Face Width:
0.045 inches
Bore Diameter:
0.090 inches both ends
Hub Style Designator:
Split first end
Hub Diameter:
0.248 inches first end
Clamping Surface Length:
0.158 inches first end
Precision Classification:
Quality number 12
Special Features:
6one hole dia. 0.048 in. Located on vertical axis 0.225 in. From center on centerline, one hole dia. 0.095 in. Located 0.095 in. Along
horizontal axis from center and 0.205 in. From center along vertical axis, teeth and bore have microinch finish 32
Material:
Aluminum alloy 2024
Material Specification:
Qq-a-225/6, t4 federal specification single material response
Surface Treatment:
Anadiza

Surface Treatment Specification:
Mil-a-8625, type 1 military specification single treatment response

NSN 3020-00-526-9608

Spur Gear - Page 2 of 2



Style Designator:
Protruding hub
Shelf Life:
N/a
Unit Of Measure:
Barrellia de la companya della companya de la companya de la companya della companya della companya de la companya de la companya della compa
Demilitarization:
No

Mil-std (military Standard):

Mil-a-8625 spec.