## NSN 3020-00-528-1160

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-528-1160

Body Style:					
Webbed, solid					
Attachment Method:					
Mounting hole					
Pitch Diameter:					
Between 2.9980 inches and 3.0000 inches					
Teeth Quantity:					
144					
Bore Style:					
W/counterbore both ends					
Mounting Hole Thread Series Designator:					
Unc transversely through hub, first end					
Mounting Hole Thready Qty Per Inch (tpi):					
32 transversely through hub, first end					
Mounting Hole Thread Size:					
0.138 inches transversely through hub, first end					
Mounting Hole Type And Quantity:					
2 threaded transversely through hub, first end					
Outside Diameter:					
3.041 inches					
Nominallength:					
0.422 inches					
Tooth Form:					
Standard					
Pressure Angle:					
14.5000 degrees					
Distance Between Body Face And Protruding Hub End:					
0.050 inches second end					
Face Width:					
0.125 inches					
Bore Diameter:					
0.188 inches both ends					
Counterbore Depth:					
0.078 inches second end					
Counterbore Diameter:					
0.470 inches second end					
Hub Style Designator:					
Plain second end					
Hub Diameter:					
0.498 inches second end					
Material:					
Copper alloy					

## NSN 3020-00-528-1160

Spur Gear - Page 2 of 2



_	•	_		
	irtac	_O Irα	aatm	ent:
J	ui iau	C 110	sauı	ICIIL.

Nickel

Style Designator:

Protruding hubs

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A27300