

View Online at <https://aerobasegroup.com/nsn/3020-00-528-1290>

**Outside Diameter:**

0.680 inches

**Overall Length:**

0.625 inches

**Thread Size:**

No. 6-32

**Bore Diameter:**

Between 0.186 inches and 0.188 inches

**Bore Length:**

0.625 inches

**Pitch Diameter:**

0.600 inches

**Securing Hole Quantity:**

2

**Face Width:**

0.093 inches

**Design Form:**

Plain

**Bore Type:**

Straight

**Counterbore Feature:**

Not included

**Hole Location:**

One located 0.187 in. From end

**Keying Facility:**

Not included

**Securing Method:**

Threaded hole

**Lightening Hole:**

Not included

**Protruding Hub Characteristic:**

Grooved

**Groove/step Location:**

Aa end

**Securing Location:**

Aa end

**Belt/chain/film Size For Which Designed:**

Ladder chain

**Teeth Row Quantity:**

1

**Teeth Quantity Per Row:**

10

**Hardness Rating Test Method:**

Not rated

**Bore Bearing:**

Not included

**Hub External Keyway:**

Not included

**Tooth Pitch:**

0.185 inches

**Hub End Outside Diameter And Location:**

0.500 inches aa end

**Distance From Outside Flange/rim To Hub End And Location:**

0.532 inches aa end

**First End Groove Diameter And Location:**

0.3125 inches aa end

**First End Groove Width And Location:**

0.157 inches aa end

**First End Length From Groove To End And Location:**

0.375 inches aa end

**Material:**

Brass, qq-b-636, class a-canceled

**Material:**

Copper alloy 464

**Material Specification:**

Qq-b-636, class a-canceled federal specification single material response

**Surface Treatment:**

Nickel

**Style Designator:**

Plain

**Surface Treatment:**

Nickel plated

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

T353-c