# NSN 3020-00-528-1292

Sprocket Wheel - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-528-1292

Outside Diameter:
0.680 inches
Overall Length:
Between 0.370 inches and 0.375 inches
Bore Diameter:
Between 0.250 inches and 0.252 inches
Bore Length:
Between 0.370 inches and 0.375 inches
Pitch Diameter:
0.600 inches
Face Width:
0.093 inches
Design Form:
Plain
Bore Type:
Straight
Counterbore Feature:
Not included
Keying Facility:
Not included
Lightening Hole:
Not included
Protruding Hub Characteristic:
Plain
Belt/chain/film Size For Which Designed:
Ladder chain
Teeth Row Quantity:
1
Teeth Quantity Per Row:
10
Hardness Rating Test Method:
Not rated
Bore Bearing:
Not included
Hub External Keyway:
Not included
Tooth Pitch:
0.185 inches
Hub End Outside Diameter And Location:
0.375 inches aa end
Distance From Outside Flange/rim To Hub End And Location:
0.257 inches aa end and 0.262 inches aa end

# NSN 3020-00-528-1292

Sprocket Wheel - Page 2 of 2



#### Material:

Brass, qq-b-636, class b-canceled

#### Material:

Copper alloy 482

## Material Specification:

Qq-b-636, class b-canceled federal specification single material response

### Surface Treatment:

Nickel

### Style Designator:

Plain

# Surface Treatment:

Nickel plated

Shelf Life:

N/a

#### Unit Of Measure:

--

#### Demilitarization:

No

### Fiig:

T353-c