## NSN 3020-00-528-1370

Spur Gear Sector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-528-1370 **Attachment Method:** Mounting hole **Teeth Quantity:** 27 Pitch Radius: 5.4500 inches **Hardness Rating:** 30.0 rockwell c and 38.0 rockwell c **Mounting Hole Type And Quantity:** 3 plain axially through body, first end and 2 plain axially through body, first end **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees **Body Recess Depth:** 0.505 inches first end **Face Width:** 0.760 inches **Outside Radius:** 5.514 inches **Precision Classification:** Quality number 10 Arc Length: 8.650 inches **Mounting Hole Diameter:** 0.285 inches axially through body, first end and 0.030 inches axially through body, first end **Bolt Hole Circle Diameter:** 3.912 inches axially through body, first end and 4.125 inches axially through body, first end **Special Features:** Bottom flange 0.255 in thick for mtg holes Material: Steel **Material Specification:** Qq-s-626, comp 8620 federal specification single material response or qq-s-624, cond normalized federal specification single material response **Style Designator:** Hubless, recessed body Shelf Life: N/a **Unit Of Measure:** 

No

Demilitarization:

## NSN 3020-00-528-1370

Spur Gear Sector - Page 2 of 2



Fiig:

A27300