## NSN 3020-00-528-4911

Sprocket Wheel - Page 1 of 2

Between 0.860 inches and 0.880 inches

**Outside Diameter:** 

**Overall Length:** 



View Online at https://aerobasegroup.com/nsn/3020-00-528-4911

0.302 inches
Thread Size:
No.8-32
Bore Diameter:
Between 0.252 inches and 0.254 inches
Bore Length:
0.302 inches
Pitch Diameter:
0.710 inches
Securing Hole Quantity:
2
Furnished Items And Quantity:
Setscrews, 2
Face Width:
Between 0.080 inches and 0.088 inches
Design Form:
Plain
Bore Type:
Straight
Counterbore Feature:
Not included
Hole Location:
Located on hub 90 degrees apart
Keying Facility:
Not included
Securing Method:
Threaded hole
Lightening Hole:
Not included
Protruding Hub Characteristic:
Plain
Securing Location:
Aa end
Belt/chain/film Size For Which Designed:
Ladder chain
Teeth Row Quantity:
1
Teeth Quantity Per Row:
12

## **NSN 3020-00-528-4911** Sprocket Wheel - Page 2 of 2



Hardness Rating Test Method:
Not rated
Bore Bearing:
Not included
Hub External Keyway:
Not included
Tooth Pitch:
0.185 inches
Hub End Outside Diameter And Location:
0.4380 inches aa end
Distance From Outside Flange/rim To Hub End And Location:
0.2190 inches aa end
Material:
Brass
Material:
Copper alloy
Surface Treatment:
Nickel
Style Designator:
Plain
Surface Treatment:
Nickel plated
Shelf Life:
N/a
Unit Of Measure:
<del>-</del>
Demilitarization:
No
Fiig:
T353-c