
NSN 3020-00-528-6805

Sprocket Wheel - Page 1 of 2





Outside Diameter: 9.725 inches **Bolt Circle Diameter:** 5.501 inches **Bore Diameter:** Between 4.4995 inches and 4.5005 inches **Bore Length:** Between 0.374 inches and 0.376 inches **Drilled Hole Diameter:** Between 0.594 inches and 0.625 inches Pitch Diameter: 9.713 inches Securing Hole Quantity: 6 or 2 Face Width: 1.750 inches Guide: Included **Design Form:** Webbed Bore Type: Straight **Groove Quantity:** 1 **Counterbore Feature:** Not included **Groove Position:** In center **Hole Location:** Located on side of sprocket **Guide Type:** Groove **Keying Facility:** Included **Securing Method:** Drilled hole Lightening Hole: Not included Securing Location: Aa end or bb end Belt/chain/film Size For Which Designed: Silent chain

NSN 3020-00-528-6805 Sprocket Wheel - Page 2 of 2



Teeth Row Quantity:
1
Teeth Quantity Per Row:
61
Hardness Rating Test Method:
Rockwell
Teeth Hardness Rating:
Between 79.0 rockwell a and 81.0 rockwell a
Bore Bearing:
Not included
Tooth Pitch:
0.500 inches
Hub End Outside Diameter And Location:
7.250 inches aa end
Distance From Outside Flange/rim To Hub End And Location:
0.687 inches aa end
Special Features:
Two holes 1/2 in20 thd size located on 5.501 in. Diameter bolt circle
Material:
Steel, sae 1117
Material:
Steel comp 1117
Material Specification:
Sae 1117 assn standard single material response
Style Designator:
Webbed or spoked
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
T353-c