

View Online at <https://aerobasegroup.com/nsn/3020-00-528-7861>

Groove Depth:

0.6879 inches

Groove Width:

0.675 inches

Outside Diameter:

Between 5.030 inches and 5.050 inches

Keyway Width:

Between 0.1883 inches and 0.1887 inches

Thread Size:

5/16-18

Bore Diameter:

Between 0.9832 inches and 0.9842 inches

Bore Length:

0.875 inches

Distance From Center Of Bore To Bottom Of Keyway:

Between 0.5614 inches and 0.5729 inches

End Application:

Engine, series 71, general motors corp

V Groove Angle In Deg:

36.0

Pitch Diameter:

4.375 inches

Securing Hole Quantity:

2

Furnished Items And Quantity:

N/a

Material And Location:

Iron, cast

Face Width:

1.625 inches

Design Form:

Webbed

Bore Type:

Straight

Bearings:

Not included

Groove Quantity:

2

Counterbore Feature:

Not included

Hole Location:

Located 180 degrees apart on pulley between hub and face 2-5/8 in. C to c

Keying Facility:

Included

Keying Facility Type:

Keyway

Securing Method:

Threaded hole

Split Hub Feature:

Not included

Web/spoke Relationship To Face Centerline:

Not offset

Lightening Hole:

Not included

Integral Cooling Vane:

Not included

Groove Shape:

V

Bore Feature:

Included

Securing Location:

Aa end

Hub End Outside Diameter And Location:

1.500 inches both ends

Distance From Outside Flange/rim To Hub End And Location:

0.750 inches both ends

Quantity:

1

Style Designator:

Webbed or spoked

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T353-a