

View Online at <https://aerobasegroup.com/nsn/3020-00-528-7861>

**Groove Depth:**

0.6879 inches

**Groove Width:**

0.675 inches

**Outside Diameter:**

Between 5.030 inches and 5.050 inches

**Keyway Width:**

Between 0.1883 inches and 0.1887 inches

**Thread Size:**

5/16-18

**Bore Diameter:**

Between 0.9832 inches and 0.9842 inches

**Bore Length:**

0.875 inches

**Distance From Center Of Bore To Bottom Of Keyway:**

Between 0.5614 inches and 0.5729 inches

**End Application:**

Engine, series 71, general motors corp

**V Groove Angle In Deg:**

36.0

**Pitch Diameter:**

4.375 inches

**Securing Hole Quantity:**

2

**Furnished Items And Quantity:**

N/a

**Material And Location:**

Iron, cast

**Face Width:**

1.625 inches

**Design Form:**

Webbed

**Bore Type:**

Straight

**Bearings:**

Not included

**Groove Quantity:**

2

**Counterbore Feature:**

Not included

**Hole Location:**

Located 180 degrees apart on pulley between hub and face 2-5/8 in. C to c

**Keying Facility:**

Included

**Keying Facility Type:**

Keyway

**Securing Method:**

Threaded hole

**Split Hub Feature:**

Not included

**Web/spoke Relationship To Face Centerline:**

Not offset

**Lightening Hole:**

Not included

**Integral Cooling Vane:**

Not included

**Groove Shape:**

V

**Bore Feature:**

Included

**Securing Location:**

Aa end

**Hub End Outside Diameter And Location:**

1.500 inches both ends

**Distance From Outside Flange/rim To Hub End And Location:**

0.750 inches both ends

**Quantity:**

1

**Style Designator:**

Webbed or spoked

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

T353-a