NSN 3020-00-531-0658

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-531-0658

Body Style:
Plain, solid
Pitch Diameter:
Between 3.9100 inches and 3.9160 inches
Teeth Quantity:
47
Bore Style:
W/ keyway both ends
Hardness Rating:
30.0 rockwell c and 36.0 rockwell c
Outside Diameter:
4.067 inches
Nominallength:
0.970 inches
Tooth Form:
Standard
Pressure Angle:
14.5000 degrees
Distance Between Body Face And Protruding Hub End:
0.440 inches first end
Face Width:
0.375 inches
Bore Diameter:
0.625 inches both ends
Keyway Width:
0.124 inches both ends
Distance From Bore Center To Keyway Bottom:
0.376 inches both ends
Hub Style Designator:
Plain both ends
Hub Diameter:
1.250 inches second end
Material:
Steel
Surface Treatment:
Phosphate manganese and phosphate zinc
Surface Treatment Specification:
Mil-p-16232, type 2, class 1 military specification single treatment response and mil-p-16232, type m, class 1 military specification single
treatment response
Style Designator:
Protruding hubs
Shelf Life:
N/a

NSN 3020-00-531-0658

Spur Gear - Page 2 of 2



U	n	it	Of	Μe	eas	ur	e:

--

Demilitarization:

No

Fiig:

A27300

Mil-std (military Standard):

Mil-p-16232 spec.