NSN 3020-00-535-1431

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-535-1431

| De de Otele |
|---|
| Body Style: |
| Plain, solid |
| Attachment Method: |
| Mounting hole |
| Pitch Diameter: |
| 1.2812 inches |
| Teeth Quantity: |
| 41 |
| Bore Style: |
| W/counterbore counterbore, first end |
| Mounting Hole Type And Quantity: |
| 4 countersunk axially through body, first end |
| Outside Diameter: |
| 1.344 inches |
| Tooth Form: |
| Standard |
| Flange Diameter: |
| 1.495 inches |
| Pilot Length: |
| 0.045 inches |
| Pressure Angle: |
| 14.5000 degrees |
| Flange Thickness: |
| 0.047 inches |
| Face Width: |
| 0.188 inches |
| Bore Diameter: |
| 0.250 inches counterbore, first end |
| Distance Between Outer Body Face And Inner Flange Face: |
| 0.188 inches |
| Counterbore Depth: |
| 0.094 inches counterbore, first end |
| Counterbore Diameter: |
| 0.500 inches counterbore, first end |
| Pilot Diameter: |
| 1.304 inches |
| Mounting Hole Diameter: |
| 0.141 inches axially through body, first end |
| Bolt Hole Circle Diameter: |
| 0.880 inches axially through body, first end |
| Material: |

viatoriai.

Plastic acrylonitrile-butadiene-styrene (abs)

NSN 3020-00-535-1431

Spur Gear - Page 2 of 2



| • | _ | | | |
|-------|-----|-----|-----|------|
| Style | 1)6 | SIM | na | t∩r∙ |
| Otylo | | JIG | ııu | w. |

Flanged end with pilot

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A27300