

View Online at <https://aerobasegroup.com/nsn/3020-00-541-2848>

Groove Depth:

0.906 inches

Groove Width:

Between 0.916 inches and 0.920 inches

Outside Diameter:

22.950 inches

Overall Length:

7.000 inches

Keyway Width:

0.500 inches

Thread Size:

5/8-11

Bore Diameter:

Between 2.000 inches and 2.001 inches

Bore Length:

7.000 inches

Distance From Center Of Bore To Bottom Of Keyway:

1.250 inches

V Groove Angle In Deg:

38.0

Pitch Diameter:

22.000 inches

Securing Hole Quantity:

2

Material And Location:

Aluminum alloy, qq-a-596, t65

Face Width:

6.375 inches

Design Form:

Webbed

Bore Type:

Straight

Bearings:

Not included

Groove Quantity:

6

Counterbore Feature:

Not included

Hole Location:

One hole located on top of key, one hole 90 degrees from keyway

Keying Facility:

Included

Keying Facility Type:

Keyway

Securing Method:

Threaded hole

Split Hub Feature:

Not included

Web/spoke Relationship To Face Centerline:

Not offset

Lightening Hole:

Included

Integral Cooling Vane:

Not included

Groove Shape:

V

Standard V-belt Section Designation For Which Designed:

C

Bore Feature:

Included

Securing Location:

Both ends

Hub End Outside Diameter And Location:

4.500 inches both ends

Distance From Outside Flange/rim To Hub End And Location:

0.313 inches both ends

Special Features:

1 hole 17/32 in. Drill in v-belt groove, concentric w/securing hole located in top of key

Quantity:

1

Style Designator:

Webbed or spoked

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T353-a