## NSN 3020-00-541-3834

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-541-3834 **Body Style:** Webbed, with lightening holes Pitch Diameter: 4.5000 inches **Teeth Quantity:** 72 **Bore Style:** W/ keyway both ends Hardness Rating: 28.0 rockwell c and 33.0 rockwell c **Outside Diameter:** 4.623 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees Distance Between Body Face And Protruding Hub End: 0.312 inches first end **Face Width:** 0.500 inches **Bore Diameter:** 0.62535 inches both ends **Keyway Width:** 0.125 inches both ends **Distance From Bore Center To Keyway Bottom:** 0.3905 inches both ends **Hub Style Designator:** Plain both ends **Hub Diameter:** 1.125 inches both ends **Special Features:** Pitch 0.19635 in. Circular; outside dia. 4.621 min 4.625 maximum in.; bore dia. 0.6250 min 0.6255 maximum in.; bore lg 0.812 in. Nom; web location: on gear teeth centerline; Ig 0.812 in. Nom Material: Steel **Material Specification:** Qq-s-624 federal specification single material response **Style Designator:** 

--

N/a

Shelf Life:

**Unit Of Measure:** 

One protruding hub, one flush hub

## NSN 3020-00-541-3834

Spur Gear - Page 2 of 2



Demilitarization:

No

Fiig:

A27300